



Document

AMDS.0021.v01

September 2020

Item code

Code FA.D01.S.0021

SKU AM.0021

Key features

Hospital-grade, sturdy

All stainless steel body

Engineered in Switzerland

Contactless, electronic



Alus Med Ltd.

Unit 3.1, Bank Studios

Park Royal Road

London NW10 7LQ

United Kingdom

Alus Med Gulf LLC

Office 1101- 11th floor

Julphar Towers

Ras al Khaimah

United Arab Emirates

+44 20 3397 1350

+971 7 226 4848

info@alusmed.com

www.alusmed.com

Data sheet

STAYSAFE Automatic hand sanitation unit



Features

- Surgical grade, electronic touchless hand disinfection chemicals dispenser
- Entirely built in stainless steel, available in polished or brushed versions
- Available also in painted steel in a color of client's choice
- Embeds a replaceable 5 liters sanitation agent tank, as per industry standards
- Tank is key-locked in the dispenser's head to avoid tampering and removal
- Completely automatic dosing and chemical delivery, contactless
- Disinfectant quantity: 1ml per dose- one tank delivers 5,000 doses
- Doses are adjustable in steps of 0.1ml
- Available with full-height stand or head-only, for wall installation
- Optional message-plate holder on top of dispensing head
- Battery operated: a charge delivers 10,000 doses, battery recharges in 6 hours
- 24-months international warranty
- On-site Alus Med service

Technical specifications

- Sturdy construction entirely in laser-cut stainless steel AISI 316
- Suitable for steam-cleaning as per Hospital specifications
- Brushed steel or clear, polished mirror versions
- Painted version, in steel with double powder coating within the RAL palette
- Proprietary electronic board, sensors and components, all made in Europe
- Adjustable parameters: duration of spray, interval between sprays, quantity of chemical agent dispensed per dose
- Standard dispensing dose 1 ml (5,000 doses per 5l tank)
- Dispensing dose adjustable in steps of 0.1 ml
- Battery operated- internal rechargeable battery lasting 10,000 doses
- Battery recharge average time: 6hours
- Battery charger included: 110-220V, 6.9V, 1.4A
- CE certification, made in production plant certified ISO9000
- Full height version with stand: cm 152.5 x 45 x 45 - Weight 21.7 Kg
- Wall-mount version (head only): cm 69 x 20 x 20 - Weight 16 Kg